



When it comes to waterproofing decks and flat roofs...
We've Got You Covered!

PRODUCT DATA SHEET

Duradek Ultra PVC Sheet Membrane

Duradek is an outdoor vinyl flooring system that provides an attractive, finished walking surface and roof-grade waterproofing in a single-ply, single product solution.

Since 1974 over 145 million square feet of Duradek outdoor vinyl flooring has been successfully waterproofing sun decks, balconies, roof decks and more.

The Duradek system is easily integrated into the building envelope to assist in managing water away from the structure, thus protecting the building and extending its life.

DURADEK ULTRA PRODUCT FEATURES

- 60 mil thickness
- 10 year waterproofing warranty
- 5 year appearance warranty
- Textured for slip resistance - meets ADA requirements
- UV and mould inhibitors for extended life
- Useable immediately after installation (no curing time)
- Only maintenance is occasional cleaning (no re-coating needed)
- ICC listed as a Thermoplastic Roofing Membrane (AC 75) and a Pedestrian Traffic Coating (AC 39)
- Class A & C Fire Rating
- Expands and contracts with substrate without cracking (tested to -40 ± 1°C)
- Installed only by authorized and trained contractors using sound roofing details
- Specially formulated adhesives and color coordinated trim pieces
- Over 20 color/pattern options available



Duradek Vinyl Membranes Stand the Test of Time

Since 1974, over a 145 million square feet of decks protected all over North America.

Duradek US Inc.
1722 Iron Street
N. Kansas City, Missouri, USA 64116
duradekus@duradek.com
816-421-5830 | TF 1-800-338-3568

Duradek Canada Ltd.
8288 129 Street
Surrey, British Columbia, Canada V3W 0A6
duradek@duradek.com
604-591-5594 | TF 1-866-591-5594

duradek



Manufactured in North America
www.duradek.com



When it comes to waterproofing decks and flat roofs...
We've Got You Covered!

Duradek Ultra PVC Sheet Membrane

PHYSICAL PROPERTIES

- Calendered polyvinyl chloride (PVC) film laminated to a woven, heat-set polyester fabric.
- Surface is factory printed and top-coated with a PVC/acrylic finish
- Weight: 55 oz. per sq. yd. (1864 g/m²)
- Thickness: nominally 0.060 inch [60 mils (1.5 mm)]
- Width: 72 inch (182.88 cm)
- Length: master rolls 25 yards (22.86 m) / or cut to order

TESTS & EVALUATIONS

Code Compliance	ICC-ES No. 2151	Thermal and Moisture Protection Evaluation Report Compliance with 2009 and 2012 IBC & IRC - Section 07 18 13 Pedestrian Traffic Coatings - Section 07 54 00 Thermoplastic Roofing Membrane - Section 07 54 19 Polyvinyl Chloride Roofing
	FBC Report No. FL12407	Compliance with 2014 Florida Building Code
	TDI Report No. RC-477	Meets Texas Department of Insurance Requirements
	CGSB QAI Report No. RJ0449P-1R1	Compliance with CAN/CGSB 37.54-95 - Polyvinyl Chloride Roofing & Waterproofing Membrane Type 3, Class B
	CCMC Report No. 13134-R	Compliance with 2010 NBC - Traffic Coating and Walkable Roofing Membrane over Habitable or Rated Space.
Independent Quality Control	QAI Listing No. B1023-2	Quality Auditing Institute - an accredited third party product certification body to ensure consistent product quality.
Fire Classification	QAI Engineering Evaluation RJ0720F-1 & RJ5052F-1	ASTM E108-08 Fire test of roof covering methods. - Class A and Class C fire rating.
	QAI Engineering Evaluation T731-2 & T731-8	CAN/ULC S107-3 Methods of fire tests of roof coverings. - Class A and Class C fire rating.
Wind Uplift	QAI Test Report No. RJ0913P-1R2	Passed ANSI/FM 4474 (2004) - to evaluate the wind uplift resistance of roof assemblies.
Edge Flashing Pulloff Resistance	Farabaugh Test Report No. T128-11	Passed ANSI/SPRI ES-1 wind design standard - for edge systems used with low slope roof systems.



For Test Report details, Detail Drawings or MSDS please visit
www.duradek.com/architectural-resources/vinyl-decking-resources

Duradek US Inc.
 1722 Iron Street
 N. Kansas City, Missouri, USA 64116
duradekus@duradek.com
 816-421-5830 | TF 1-800-338-3568

Duradek Canada Ltd.
 8288 129 Street
 Surrey, British Columbia, Canada V3W 0A6
duradek@duradek.com
 604-591-5594 | TF 1-866-591-5594

duradek



Manufactured in
 North America
www.duradek.com